

SG-AL5、SG-AL4K、SG-B1、SG-B2、SG-B5

仕様・価格(本体)

型式	SG-AL5		SG-AL4K		SG-B1		SG-B2		SG-B5												
外観																					
種類	露出形		埋込形		分電盤協約形サイズ																
警戒回路数	1回路				1回路																
電源電圧	AC100V-200V 50/60Hz				AC100V、AC200V 50/60Hz	AC200V、AC415V 50/60Hz	AC100V、AC200V 50/60Hz	AC200V、AC415V 50/60Hz	AC100V、AC200V 50/60Hz	AC200V、AC415V 50/60Hz											
定格感度電流	100/200/400/800/1000mA		100/200/400/800mA		30mA		100/200/500mA		200/500/1000mA												
動作時間	0.5秒				0.1秒以内(高速形)		0.1/0.3/0.5秒切替		0.1/0.3/0.5秒切替												
音響装置と音圧	内蔵電子ブザー 70dB以上				なし																
ブザー停止機能	あり				－																
復帰方式	手動復帰/自動復帰(スイッチによる切替)				手動復帰																
消費電力	常時1VA 動作時2.5VA				常時0.2W 動作時1.5W																
外部接点	無電圧 2a AC250V 1.5A DC30V 1A				<table><tr><td colspan="2">1c、1a</td></tr><tr><td></td><td>COS φ=1</td><td>COS φ=0.4</td></tr><tr><td>AC100V</td><td>5A</td><td>0.6A</td></tr><tr><td>AC200V</td><td>5A</td><td>－</td></tr></table>						1c、1a			COS φ=1	COS φ=0.4	AC100V	5A	0.6A	AC200V	5A	－
1c、1a																					
	COS φ=1	COS φ=0.4																			
AC100V	5A	0.6A																			
AC200V	5A	－																			
製品質量	約200g		約320g		約270g		約300g														
外形寸法	137×100×38.5mm (タテ×ヨコ×フカサ)		130×90×84.5mm (タテ×ヨコ×フカサ)		95×75×60(66*)mm (タテ×ヨコ×フカサ(*最頂部))																
外観色	白(マンセル8GY9.7/0.2 プラスチック製)		黒(マンセルN1.5 プラスチック製)		黒(マンセルN1.5 プラスチック製)																
ご注文品番	SGAL5		SGAL4K		SGB1	SGB14	SGB2	SGB24	SGB5	SGB54											
納期区分	◎		◎		◎	●	◎	●	◎	●											
標準価格(円)	14,700		26,500		16,900				19,400												
組み合わせる変流器	S-68(600A)以下の貫通形変流器に対応				全変流器に対応																